

VT1508T Van trailer



Specification

Gross Weight	Payload	Length	Width	Height	Overall Height	Tyre Size	Axle
1500 kg	1000 kg	2400	1600	1840	2250	155R13	2 braked

Construction

Constructed from materials that are robust, durable and damage resistant. The materials can be easily cleaned and the unit is virtually maintenance free and complete with a 12-month guarantee and warranty.

Main Features

Body design	Stylish, sleek and aerodynamic. Built from strong and robust fibreglass coated panels.
Roof	Translucent material to maximise daylight.
Chassis	Fully galvanised with lockable coupling. Carefully balanced for easy handling, hitching and towing.
Mobile stability	Twin rubber torsion axles with wheels on the outside of the body for extra stability and prevention of snaking.
Stationary stability	Rear drop legs.
Internal	Recessed lashing rings and non-slip phenolic flooring.

Optional Extras

- Spare wheel and carrier.
- Lashing rail (as an additional load restraint).
- AMS Security Mule. An approved anti-theft device. (possible savings on insurance premiums)
- Bespoke design and build to your specifications.

Accessories

Spare Wheel	£65.00
Spare Wheel Carrier	£45.00
Internal Light	£65.00
Rear Light Protection Nudge Bars	£60.00
Drop Legs (pair)	standard
Deck Rings (4 of)	standard
Side Flap	£350.00
Single Door	£250.00
Lashing Rail (per metre)	£15.00